
SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0	Revision Date 10.06.2015	Print Date 12.06.2015	GB / EN
	Date of last issue: 21.01.2015		
	Date of first issue: 21.01.2015		

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Commercial Product Name : Mitre Kit (B)
Product code : 0893900090 (B)
SDS-Identcode : 10047582

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Hardener

1.3 Details of the supplier of the safety data sheet

Company : Würth UK Ltd
1 Centurion Way
Erith, Kent
United Kingdom
Telephone : +44 (0)3300 555 444
Telefax : +44 (0)3300 555 666
Company : WÜRTH IRELAND LTD.
Monaclinoe Ind. Est. Ballysimon Road
Limerick
Ireland
Telephone : +353 61 430200
Telefax : +353 61 412428

Responsible/issuing person : E-mail address: prodsafe@wuerth.com

1.4 Emergency telephone number

National Chemical Emergency Centre
+44 (0)870 190 6777

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

Classification (67/548/EEC, 1999/45/EC)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

Extremely flammable

R12: Extremely flammable.

Irritant

R36: Irritating to eyes.

R67: Vapours may cause drowsiness and dizziness.

2.2 Label elements**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H222
H229
H319
H336Extremely flammable aerosol.
Pressurised container: May burst if heated.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary statements

:

Prevention:

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.

P211

Do not pierce or burn, even after use.

P251

Avoid breathing spray.

P261

P280

Wear eye protection/ face protection.

Storage:

P410 + P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

- isopropanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

Hazardous components

Chemical Name	CAS-No.	Classification (67/548/EEC)	Classification (1272/2008/EC)	Concentration [%]
	EC-No.			
	Registration number			
isopropanol	67-63-0	F; R11 Xi; R36 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 75 - < 80
	200-661-7			
isopentane	78-78-4	F+; R12 Xn; R65 R66 R67 N; R51-R53	Flam. Liq. 1; H224 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 0,75 - < 1
	201-142-8			
N,N-dimethyl-p-toluidine	99-97-8	R33 R52-R53 T; R23/24/25	Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT RE 2; H373 Aquatic Chronic 3; H412	>= 0,75 - < 1
	202-805-4			
	01- 2119937766- 23			

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : If you feel unwell, seek medical advice (show the label where possible). First aider needs to protect himself. Move out of dangerous area. Never give anything by mouth to an unconscious person. Take off contaminated clothing and shoes immediately.
- If inhaled : If breathed in, move person into fresh air. In the case of inhalation of aerosol/mist consult a physician if necessary. Keep patient warm and at rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
- In case of eye contact : Protect unharmed eye. If easy to do, remove contact lens, if worn. In the case of contact with eyes, rinse immediately with plenty of water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

and seek medical advice.

If swallowed

: If swallowed, seek medical advice immediately and show this container or label. If swallowed, DO NOT induce vomiting. If a person vomits when lying on his back, place him in the recovery position.

4.2 Most important symptoms and effects, both acute and delayed

No data available

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Carbon dioxide (CO₂), Alcohol-resistant foam, Dry powder

Unsuitable extinguishing media : High volume water jet, Water

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products may be formed under fire conditions (see section 10). Exposure to decomposition products may be a hazard to health.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. In the event of fire and/or explosion do not breathe fumes. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Refer to protective measures listed in sections 7 and 8. Use personal protective equipment. Remove all sources of ignition. Avoid contact with skin and eyes. Ensure adequate ventilation, especially in confined areas. Immediately evacuate personnel to safe areas. Avoid inhalation of vapour or mist. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations. Clean contaminated surface thoroughly.

6.4 Reference to other sections

see chapter: 7, 8, 11, 12 and 13

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : For personal protection see section 8. Limit the stocks at work place. Use only in well-ventilated areas. Do not breathe vapours or spray mist. Avoid contact with skin and eyes. Do not spray on a naked flame or any incandescent material. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Take precautionary measures against static discharges.

Advice on protection against fire and explosion : Normal measures for preventive fire protection. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition. Do not smoke. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard.

Dust explosion class : Not applicable

7.2 Conditions for safe storage, including any incompatibilities

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

Requirements for storage areas and containers : Store in original container. BEWARE: Aerosol is pressurized. Keep away from heat. Keep away from direct sunlight. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep containers tightly closed in a cool, well-ventilated place. Please observe the storage instructions for aerosols!

Advice on common storage : Incompatible with oxidizing agents. Incompatible with acids.
Keep away from food, drink and animal feedingstuffs. Do not store together with oxidizing and self-igniting products.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

Components	CAS-No.	Control parameters	Basis	Update
isopropanol	67-63-0	TWA: 999 mg/m ³ , 400 ppm STEL: 1.250 mg/m ³ , 500 ppm	GB EH40	2006-09-01
butane	106-97-8	TWA: 1.450 mg/m ³ , 600 ppm Carc, STEL: 1.810 mg/m ³ , 750 ppm Carc,	GB EH40	2007-08-01
isopentane	78-78-4	TWA: 1.800 mg/m ³ , 600 ppm 2,	GB EH40	2007-08-01
isopentane	78-78-4	TWA: 3.000 mg/m ³ , 1.000 ppm	2006/15/EC	2009-12-19

Other information on limit values: see chapter 16

8.2 Exposure controls

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Product contains low-boiling liquids. Respiratory protective equipment must be air supplied respirators.
Respirator with filter type A
Half mask with a particle filter P2 (EN 143)

Hand protection

Material : butyl-rubber

Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.

Eye protection : Safety glasses with side-shields conforming to EN166

Skin and body protection : Flame retardant antistatic protective clothing.
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
General industrial hygiene practice.
Do not inhale aerosol.
Avoid contact with skin, eyes and clothing.
When using do not eat, drink or smoke.
Wash hands before breaks and at the end of workday.
Follow the skin protection plan.
Take off all contaminated clothing immediately.
Wash contaminated clothing before re-use.

Environmental exposure controls

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

General advice : Do not flush into surface water or sanitary sewer system.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance : aerosol
Propellant : butane, isobutane, propane
Colour : colourless
Odour : alcohol-like
Odour Threshold : No data available
Flash point : No data available
Ignition temperature : 410 °C
Thermal decomposition : No data available
Lower explosion limit : 1,8 %(V)
Upper explosion limit : 12,7 %(V)
Explosive properties : No data available
Flammability : No data available
Oxidizing properties : No oxidising effect.
Auto-ignition temperature : No data available
Burning number : No data available
Molecular weight : No data available
pH : Not applicable
Boiling point/boiling range : ca. -40 °C
Vapour pressure : No data available
Density : 0,80 g/cm³
Bulk density : No data available
Water solubility : completely miscible
Partition coefficient: n-octanol/water : log Pow: < 3
Solubility in other solvents : completely soluble
Medium: Diethylether

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

Viscosity, dynamic : No data available
Viscosity, kinematic : 6 - 10 mm²/s at 40 °C
Method: ISO 3104

Flow time : No data available
Impact sensitivity : No data available
Relative vapour density : No data available
Surface tension : No data available
Evaporation rate : No data available
Minimum ignition energy : No data available
Acid number : No data available
Refraction index : No data available
Miscibility in water : No data available
Solvent separation test : No data available

9.2 Other information

None known.

SECTION 10: Stability and reactivity**10.1 Reactivity**

No data available

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Stability : No decomposition if stored and applied as directed.
Vapours may form explosive mixtures with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon monoxide, Carbon dioxide (CO₂), Nitrogen oxides (NO_x)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Acute oral toxicity : Acute toxicity estimate : > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 5 mg/l
Test atmosphere: dust/mist
Exposure time: 4 h
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2.000 mg/kg
Method: Calculation method

Acute toxicity (other routes of administration):

No data available

Skin corrosion/irritation

isopentane : Repeated exposure may cause skin dryness or cracking.

N,N-dimethyl-p-toluidine : No skin irritation

Serious eye damage/eye irritation

isopropanol : Irritating to eyes.

isopentane : Species: Rabbit
No eye irritation
Method: OECD Test Guideline 405

N,N-dimethyl-p-toluidine : No eye irritation

Respiratory or skin sensitisation

Sensitisation:

isopentane : Species: Guinea pig
Result: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 406

Germ cell mutagenicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

Genotoxicity in vitro:

isopentane : Type: Ames test
Result: negative
Method: OECD Test Guideline 471

Genotoxicity in vivo:

isopentane : Test species: Rat
Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

STOT - single exposure

isopropanol : May cause drowsiness or dizziness.

isopentane : May cause drowsiness or dizziness.

STOT - repeated exposure

N,N-dimethyl-p-toluidine : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Aspiration toxicity

isopentane : May be fatal if swallowed and enters airways.

Neurological effects

No data available

Toxicology Assessment

Toxicology, Metabolism, Distribution

No data available

Acute effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

No data available

Further information : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Vapours may cause drowsiness and dizziness.

SECTION 12: Ecological information**12.1 Toxicity**Toxicity to fish

isopropanol : LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l
Exposure time: 96 h

isopentane : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,26 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

N,N-dimethyl-p-toluidine : LC50 (Fish): 24,335 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates

isopropanol : EC50 (Daphnia magna (Water flea)): 13.299 mg/l
Exposure time: 48 h

isopentane : EC50 (Daphnia magna (Water flea)): 2,3 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 202

N,N-dimethyl-p-toluidine : LC50 (Daphnia magna (Water flea)): 15,259 mg/l
Exposure time: 48 h

Toxicity to algae

isopentane : EC50 (Scenedesmus capricornutum (fresh water algae)): 10,7 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

N,N-dimethyl-p-toluidine : EC50 (Pseudokirchneriella subcapitata (green algae)): 24,37 mg/l
Exposure time: 72 h

Toxicity to bacteria

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

N,N-dimethyl-p-toluidine : EC50 : 42,86 mg/l
Exposure time: 48 h

Ecotoxicology AssessmentChronic aquatic toxicity

isopentane : Toxic to aquatic life with long lasting effects.

N,N-dimethyl-p-toluidine : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradabilityBiodegradability

isopentane : Result: Readily biodegradable
Method: OECD Test Guideline 301F

N,N-dimethyl-p-toluidine : Result: Readily biodegradable

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological information : The product should not be allowed to enter drains, water courses or the soil.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

Advice on disposal and packaging : Disposal:
In accordance with local and national regulations. This material and its container must be disposed of as hazardous waste.
Waste codes should be assigned by the user based on the application for which the product was used.

The following Waste Codes are only suggestions:

Waste Code (EWC) : Waste Key (unused product):
150110, packaging containing residues of or contaminated by dangerous substances

Waste key (used product):
150110, packaging containing residues of or contaminated by dangerous substances

Disposal of uncleaned packaging : Waste key (uncleaned packaging):
150110, packaging containing residues of or contaminated by dangerous substances

Note: Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not burn, or use a cutting torch on, the empty drum. Please ensure aerosol cans are sprayed completely empty (including propellant) Containers that have not been emptied in compliance with regulations are regarded as hazardous waste. Dispose of as unused product.

SECTION 14: Transport information**14.1 UN number**

ADR : 1950
RID : 1950
IMDG : 1950
IATA : 1950

14.2 Proper shipping name

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

ADR

Classification Code : 5F
Labels : 2.1
Limited quantity : 1,00 L
Tunnel restriction code : (D)

RID

Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1
Limited quantity : 1,00 L

IMDG

Labels : 2.1
EmS Number : F-D, S-U

IATA

Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Labels : 2.1

14.5 Environmental hazards**ADR**

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA

Environmentally hazardous : no

14.6 Special precautions for user

see chapter: 6, 7 and 8

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

0893900090 (B) - Mitre Kit (B)

Version 2.0

Revision Date 10.06.2015

Print Date 12.06.2015

GB / EN

Date of last issue:

21.01.2015

Date of first issue:

21.01.2015

Full text of H-Statements referred to under sections 2 and 3.

H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Other information

2	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used
Carc	Capable of causing cancer and/or heritable genetic damage. The identified substances include those which: - are assigned the risk phrases 'R45: May cause cancer'; 'R46: may cause heritable genetic damage'; 'R49: May cause cancer by inhalation' or - a substance or process listed in Schedule 1 of COSHH.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Prepared by : SAP Business Compliance Services GmbH
Birlenbacher Str. 19
D-57078 Siegen
Germany
Telephone: +49-(0)271-88072-0

Ref.: WGB10000561
